## PrecisionColor Pivot

Radius' PrecisionColor™ Pivot® is a highly versatile and cost-efficient Macintosh monitor solution that lets you look at your everyday business applications in unique new ways.

With the 15-inch PrecisionColor Pivot in the portrait position, you can generate word proces sing output such as letters, contracts, and memos. With a quick flip to the landscape position, vou can create spreadsheets, charts, graphs, and presentations. And you won't have to worry about any drop-off in productivity because you don't need to log-off or shut down the display while switching between landscape and portrait applications.

The PrecisionColor Display offers a variety of resolutions for full-page views — with nearly 17 million vivid colors on the family of Macintosh systems. Pivoting, ergonomic design, and outstanding image focus and clarity come standard with the PrecisionColor Pivot, meaning that no additional investments have to be made to achieve the flexibility you need.



## A Horizontal (and Vertical) Approach to the Desktop

#### The freedom to choose

Because the PrecisionColor Pivot can be used in portrait and landscape orientations. you can present your documents in the view best suited for your application. Portrait mode is ideal for word processing and general text tasks. In an instant, you can conveniently tilt the display to landscape mode for spreadsheets and presentations.





#### Built-in video compatibility

Because a video interface card is built into the Macintosh, you won't need to make an additional investment if you connect the Pivot display to Centris, Quadra, and certain LC and Performa systems.

## Affordable price in 15 inches

With a pixel density of 832 x 624, the 15-inch PrecisionColor Pivot offers the same resolution as more expensive 16" and 17"

displays. Its color screen delivers a page of crisp text, numbers, and colorful graphics for expanded views - without forcing you to reduce or scroll through the screen.

### **Ergonomically designed**


To optimize user comfort and ease-of-use, the PrecisionColor Pivot is designed to conform to worldwide guidelines such as the Swedish MPR II standards. That means that the display, with low-emissions, an anti-glare screen, and tilt/swivel base, can be



ergonomically incorporated into all areas of your office environment.

### Unique service/support programs

On that very rare occasion when your PrecisionColor Pivot Display fails, Radius will provide free overnight delivery and on-site replacement<sup>1</sup>. It's called Worry-Free Warranty, and it's the foundation of Radius' awardwinning commitment to customer service. Our priority is to deliver timely, hassle-free support programs that minimize downtime and maximize your productivity. Just dial 408/434-1012.





# PrecisionColor Pivot

## S P E C I F I C A T I O N S

**CRT** 

Display size: 15 inches diagonal, F.S. tube design

Phosphor type: P29

Image size: 10.63 in (270 mm) x 7.87 in (200 mm)

Face treatment: SFC anti-glare and anti-static coatings

Resolution: From 640 x 480 to 1024 x 768 (see matrix)

Dot Pitch: .28mm dot-trio

Pixel density: 78 dpi 832 x 624; 81 dpi 864 x 640; 96 dpi 1024 x 768

Video

Video signal: RS-343A, 75ohm terminated analog red, green, and blue

Sync: Separate H sync and V sync

TTL: Negative polarity
Horizontal scan range: 30-60 KHz

Vertical refresh rates: 50-90 Hz (Up to 72Hz at 1024 x 768, 75 Hz at 864 x 640)

**Physical Attributes** 

Width: Portrait: 12.5 in (318 mm) Landscape: 15 in (381 mm)

Height: Portrait: 18.0 in (457 mm)

Landscape: 16.5 in (419 mm)
Depth: 17.0 in (432 mm)

Weight: 47.9 lbs. (21.8 kg), Tilt/Swivel/Pivot included

User Controls: Brightness, contrast, power, vertical and horizontal centering and sizing

**Power** 

Input voltage range: 100 to 240 VAC self configuring

Frequency: 47 to 63 Hz

**Environmental** 

Operating temperature: 50 ° to 97° F (10° to 35° C)

Humidity: 10% to 80%

Altitude: 10,000 ft. (3,000 meters) maximum

**Regulatory Approvals** 

Safety: UL, CSA, TUV

RFI: FCC B, Canadian DOC B, VFG 243, VCCI Class 2

**Ergonomics** Meets or exceeds MPR II guidelines, SWEDAC, ISO 9241

Part Number PrecisionColor Pivot - 0356

For the Radius Authorized Reseller or Distributor nearest you, call (800) 227-2795 (U.S. & Canada only) or (408) 434-1010 or Fax (408) 434-0127 (International only).

© 1993 Radius Inc. Radius, the Radius logo, and all product names are trademarks of Radius Inc. Other brand and product names are trademarks or registered trademarks of their respective holders. Product specifications are subject to change without notice. Part Number: DS0356. (10-93) Created by Radius Design using Radius PrecisionColor Display/20v with a PrecisionColor Pro 24X and Rocket 33 on a Macintosh Ilci.

MACINTOSH		640 x 480 Apple 13" Resolution	832 x 624 Apple 16" Resolution	864 x 640 Full Page Resolution	1024 x 768 Two Page Resolution
Quadra 950, 900, 700¹	8-bit	Color Pivot-II Interface 0406	No Interface Required. Built-in Video <sup>1</sup>	Color Pivot-II Interface 0406	PrecisionColor 8XJ Interface 0369
	24-bit	PrecisionColor Pro 24XP 0431	No Interface Required. Built-in Video <sup>1</sup>		PrecisionColo 24XK Interface 0422
Quadra 800 <sup>1</sup> , 650 <sup>1</sup> Centris 650 <sup>1</sup>	8-bit	Color Pivot-II Interface 0406	No Interface Required. Built-in Video <sup>1</sup>	Color Pivot-II Interface 0406	PrecisionColo 8XJ Interface 0369
	16-bit		No Interface Required. Built-in Video <sup>1</sup>		
	24-bit	PrecisionColor Pro 24XP 0431	PrecisionColor Pro 24XP 0431		PrecisionColor 24XK Interface 0391
Quadra 610 Centris 610'	8-bit		No Interface Required. Built-in Video <sup>1</sup>		
	16-bit		No Interface Required. Built-in Video <sup>1</sup>		
	24-bit	PrecisionColor Pro 24XP 0431	PrecisionColor Pro 24XP 0431		PrecisionColor 24XK Interface 0422
Other NuBus Performa 600 Ilvi, Ilvx, Ilfx, Ilci, Ilcx, Ilx, II and Ilsi²	8-bit	Color Pivot-II Interface 0406	Color Pivot-II Interface 0406	Color Pivot-II Interface 0406	PrecisionColo 8XJ Interface 0369
	24-bit	PrecisionColor Pro 24XP 0431	PrecisionColor Pro 24XP 0431		PrecisionColo 24XK Interface 0422
Quadra 605, LC III, 475	8-bit		No Interface Required. Built-in Video <sup>1</sup>		
	16-bit		No Interface Required. Built-in Video <sup>1</sup>		
Classic II, PowerBook 140, 145, 170	8-bit		PowerView 0366		
PowerBook 160, 165c, 180, Duo 210, 230, 250, 2	8-bit		Built-in Video <sup>3</sup>		

<sup>&</sup>lt;sup>1</sup> Additional Apple VRAM may be required for some configurations

Pivoting Capability Landscape Mode Only



<sup>&</sup>lt;sup>2</sup> Radius Interfaces for the Ilsi requires a Nubus adapter card

<sup>&</sup>lt;sup>3</sup> PowerBook DuoDock or PowerBook MiniDock required